Benchmark Vortex Mixer Senchmark Vortex Mixer



- Powerful Motor for INSTANT Vortexing
- ightharpoonup Touch or Continuous Operation





Technical Data

Speed Range: 200 to 3200 rpm
Operating Modes: Touch or continuous
Operating Temp. Range: +4 C to +65 C
Dimensions: 13 x 16 x 17 cm
5 x 6.3 x 6.7 in.
Weight: 3.8 kg/8.4 lb

Electrical: 115VAC, 60 Hz, 1.5A 230VAC, 50 Hz, 0.75A Warranty: 2 years

The **BenchMixer**[™] sets the new standard in vortex mixing. With advanced Q-Drive[™] technology, the **BenchMixer**[™] provides smooth instant vortexing of even the largest sample sizes, including full 50ml tubes. The unique counter balance system creates maximum

vortexing action, while minimizing noise and excessive vibration. This results in quieter, more efficient and longer lasting operation.

Other features include: "no-walk" suction feet, cold room/incubator compatibility and spill-proof electronic controls.

Ordering Information

BV1000* BenchMixer Vortex Mixer

BV1000-FLAT BV1000-COMBO

Optional 3 inch flat head

Optional combination head for tubes and microplates. Holds 66 tubes (38 x 1.5ml and 28 x 0.5ml) or one microplate

* To order a product in 230V, please add -230 to item number.

Your Distributor is:





781-917-9526 www.braintreesci.com