

Core Compact Portable Balances



 **BRAINTREE
SCIENTIFIC, INC.**
LAB RESEARCH PRODUCTS

Your Distributor is:
Braintree Scientific, Inc.
PO Box 850498, Braintree, MA 02185
781-917-9526
Email: Info@braintreesci.com
Web: www.braintreesci.com



PERFECT BALANCE
Speed, Performance, Value

CQT Highlights:



Smart housing design lets you stack Core balances on top of each other for convenient storage.

Built in security slot accommodates a standard Kensington™ type lock and cable to keep your balance where you want it.

Three-point ShockProtect™ protection designed for the ultimate in performance reliability. Using ShockProtect™ your balance can withstand up to 400lb of weight without damaging the weighing mechanism.

Battery operated with 6 AA batteries. (AC adapter supplied, batteries optional.)

Compact and durable Core balances are suitable for a variety of applications.

Features

- Stainless steel pan
- Three-point ShockProtect™ overload protection
- Built in security slot for Kensington™ type lock
- Dual tare keys, color-coded for easy recognition
- Battery powered with 6 x AA batteries or AC adapter
- Auto power off to save battery life
- Low-battery indicator
- Large backlit display is clear and quick to read
- Removable draft shield on 4.7" / 120mm ø pans
- Stacking storage (CQT202, 251, 601 and 1501 models)




Backlit display

Simple keypad with dual tare keys and a bright backlit display make Core balances easy to use.



Stainless steel top pan

Removable top pan for quick clean ups and durability.



ShockProtect™ protection

Unique patented protection helps safeguard the balance from overloads.

Technical Specifications

Model	CQT 202	CQT 251	CQT 601	CQT 1501	CQT 2601	CQT 2000	CQT 5000
Capacity	200g	250g	600g	1500g	2600g	2000g	5000g
Readability	0.01g	0.1g	0.1g	0.1g	0.1g	1g	1g
Repeatability (S.D.)	0.01g	0.1g	0.1g	0.1g	0.1g	1g	1g
Linearity (+/-)	0.02g	0.1g	0.1g	0.2g	0.2g	1g	1g
Pan Size	4.7" / 120mm ø				5.7" / 145mm ø		
Weighing Units	kg / g / lb / oz / ct / dr / GN / N						
Stabilization Time	3 sec	2 sec		3 sec		2 sec	
Calibration	External Calibration						
Display	6 digit LCD, 0.6" / 18mm digits, with backlight						
Power Supply	12VAC @ 150mA adapter or 6x AA batteries						
Operating Temperature	0°C to 40°C / 32°F to 104°F						
Housing	ABS plastic						
Draft shield dimensions	5.2" ø x 3.9" / 132mm ø 100mm						
Overall Dimensions	6.7" x 9.6" x 3.1" / 170mm x 245mm x 80mm						
Net Weight	2lb / 0.9kg						

Accessories

- In-use cover
- Hard carry case
- Kensington™ type lock and cable

Your Distributor is:

Braintree Scientific, Inc.

PO Box 850498, Braintree, MA 02185

781-917-9526

Email: Info@braintreesci.com

Web: www.braintreesci.com